

## DECLARATION OF PERFORMANCE

No. 009CPR06-06-2014

## NEOLITH 12mm

1. Product type for identification: **Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0,5\%$**
2. Intended use: For internal and external wall/ceiling finishes and floorings
3. Manufacturer: THESIZE Surfaces, S.L.  
P.I. Camí Fondo, Supoi 8  
C/ Dels Ibers 31, 12550 Almassora (Castellón), Spain.
4. Systems of assessment and verification of constancy of performance (AVPC) System 3 & 4
5. Name and identification number of notified laboratory: Instituto de Tecnología Cerámica, notified laboratory number 1605 has performed the testing for the determination of the emission of hazardous substances (lead and cadmium), subject to system 3 and issued the tests reports no. C140268 through C140285 dated 26th of February 2014.
6. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
<b>Reaction to fire</b>	A1/A1 <sub>FL</sub>	<b>EN 14411:2012</b>
<b>Release of dangerous substance, for:</b>		
- Cadmium	< 0,001 mg·dm <sup>-2</sup>	
- Lead	< 0,01 mg·dm <sup>-2</sup>	
<b>Breaking strength</b>	> 6000 N	
<b>Slipperiness:</b>		
Static coefficient of friction - wet	0,43 – 0,67	
- dry	0,76 – 0,94	
<b>Thermal shock resistance</b>	Pass	
<b>Durability for:</b>		
- internal use	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Jacco Jurrissen, Quality Manager

Almassora, June 2013